

MATERIAL SAFETY DATA SHEET

BAZOOKA Spot Remover A trademark of the EDIC Corporation

Section 1 PRODUCT & COMPANY IDENTIFICATION

Product Name: Bazooka Spot Remover
Product Use: Carpet and fabric spot cleaning. Removal of oil, tar, grease adhesive, chewing gum, etc. from carpet, upholstery, fabric and other surfaces.
PIN Number: UN 1956
Distributor: The EDIC Corporation, 1753 Blake Avenue, Los Angeles, CA 90031
For Information: 800/338-3342 (8am-5pm Mon.-Fri. PST)
In an Emergency: 877/353/6662 (7am-4pm Mon-Fri MST)
Prepared By: Paul Templin
Preparation Date: February 28, 2008

Section 2 COMPOSITION INFORMATION ON INGREDIENTS

Components: This section is confidential and provided on signature of a non-disclosure and non-compete agreement.

Section 3 HAZARDS IDENTIFICATION

Emergency Overview: Avoid heating. High temperatures may cause aerosol cans to become explosive and projectiles.

Primary Routes of Entry: Skin and oral.

Physical: Combustible.

Health Hazard: Skin and eye irritant.

Acute Exposure

Eye: Contact with liquid may cause severe irritation. Contact with aerosol may cause mild irritation.

Skin: Contact for a few hours not expected to cause difficulty. Prolonged contact may result in local redness, irritation, and swelling.

Ingestion: Small amounts from fingers and hands not expected to cause problems. Large quantities may cause stinging, burning sensation, nausea, vomiting and diarrhea.

Vapor Inhalation: Not considered a hazard.

Chronic Exposure: Not known.

Sensitization: Not known

Carcinogenicity Listings: NPT-None, IARC-None, ACGIH-None.

Signs and Symptoms: Overexposure may cause pain and redness at the point of contact.

Medical Conditions: Contact with skin may aggravate a pre-existing dermatitis.

Aggravated by Exposure: Inhalation of aerosol may aggravate asthma and inflammatory lung disease.

Section 4 FIRST AID PROCEEDURES

| | |
|-------------|--|
| Eye: | Remove any contact lenses, then immediately flush with water for at least 15 minutes. If irritation persists, contact a physician. |
| Skin: | Remove contaminated clothing. Wash skin thoroughly with soap and water. If irritation persists, contact a physician. |
| Ingestion: | Give no more than two glasses of water. Do not induce vomiting. Immediately contact a Physician. |
| Inhalation: | Remove to fresh air. If needed, obtain medical help. |

Section 5 FIRE AND EXPLOSION HAZARD

| | |
|--|--|
| Flash Point and Method: | (Aerosol) Considered flammable under Consumer Safety Commission Regulations. 16 CFR 1500.3a (VII). (Concentrate) 205 Deg. F C.O.C. (Bases on an analogous formulation). ASTM D-92. |
| Auto Ignition | (Concentrate) 675 degrees. (Based on an analogous formulation.) ASTM D-92. |
| Explosion Limits: | (Concentrate) Lel-18%, Uel-Unknown. (Based on an analogous formulation.) Method used unknown. |
| Flammability Classification As Defined by OSHA | (Concentrate) Combustible. |
| Combustion Products: | As with any organic material, combustion will produce carbon dioxide and/or carbon Monoxide. |
| Extinguishing Media: | Water fog, carbon dioxide, dry chemical, foam. |
| Unusual fire and Explosion Hazard | High temperatures may cause aerosol cans to become explosive and projectiles. May produce dense, black smoke. |
| Special Fire-Fighting Precautions: | Stay up wind of a fire. Aerosols should be moved from a high temperature area immediately |
| Fire-Fighting Equipment | In closed arca, usc self-contained breathing apparatus (SCBA) |

Section 6 ACCIDENTAL RELEASE MEASURES

| | |
|---|---|
| Procedures for Clean-up: For Small Spills: | Take up with suitable absorption materials, such as sand or soil and discard in a suitable waste container. |
| Personal Precautions: | Use appropriate eye protection and avoid the inhalation of any mists. |
| Environmental Precautions: | Do not allow large amounts to enter public water way. |

Section 7 HANDLING AND SAFE STORAGE

| | |
|---|--|
| Safe Handling and Hygienic the reach of | Keep away from open flame or other ignition sources. Keep out of |
|---|--|

Practices:
Storage Requirements:

children.
Store below 120 degrees feirinheit.

Section 8 EXPOSURE CONTROLS

Engineering Controls:

Adequate general ventilation. Otherwise no special controls.

Personal Protection:

Ventilation:

Not required under normal conditions.

Respiratory:

Protection not ordinarily required. Under conditions of mist formation use a NIOSH Mask.

Eye Protection:

Eye protection such as safety glasses, goggles, etc. recommended.

Gloves:

Under conditions of sustained and extensive contact, Nitrile or Kevlar gloves recommended.

Ingestion:

Do not ingest.

Exposure Limit Guidelines:

The aerosol mixture contains carbon dioxide, CAS Number 124-38-9, which OSHA lists (Sub Part Z-1) at a TWA of 10,000 ppm and at a STEL of 30,000 ppm. Since carbon dioxide forms a normal part of human respiration, the normal low levels of Carbon dioxide encountered should not cause concern. The regulatory limits are not normally exceeded.

Section 9 PHYSICAL & CHEMICAL PROPERTIES

Appearance and Odor:

Clear colorless, citrus odor.

Physical State:

Liquid under pressure.

Specific Gravity:

0.816, 6.81 lbs/US gallons. ASTM D-4052

Solubility in Water:

Emulsifies.

PH of Concentrate:

Not applicable.

Vapor Pressure:

(Concentrate) <0.10 mm. (Based on an analogous formulation.)
ASTM D-5191.

Boiling Point:

367 - >461 Deg. F (Based on an analogous formulation.)
ASTMD-86.

Viscosity:

(Concentrate) > 1.73 cps. (Based on an analogous formulation.)
ASTM D-445.

Vapor Density:

(Air=1)4.5. (Based on an analogous formulation.)

Percent Volatile by Volume:

88% (Estimated).

Freezing Point:

Data not available.

Evaporation Rate:

(Butyl Acetate=1) <1 (Esstimated).

Section 10 STABILITY & REACTIVITY

Stability:

Stable.

Conditions to Avoid:

Avoid high temperatures.

Incompatibility:

Avoid strong oxidizing agents.

Hazardous Decomposition:
and projectiles.

High temperatures may cause aerosol cans to become explosive

Hazardous Polymerization:

Will not occur.

Section 11 TOXICITY INFORMATION

Current information for this MSDS was developed from component data and from manufacturing experience.

Section 12 ECOLOGICAL INFORMATION

Although the testing data is not available for the product, an assessment of the components suggests that this product should not present any significant environmental impact. Product expected to biodegrade in the environment. See the section on Disposal Consideration for guidelines.

Section 13 DISPOSAL CONSIDERATIONS

RCRA:

Waste Classification:

Product has been evaluated for RCRA classification and does not meet criteria of a hazardous waste if discarded in a vented form.

Volatile Organic Compound:

VOC content estimated at 12 wt.%. Product may find exemption under regulations. Consult local authorities for appropriate compliance.

Special Instructions:

Industrial users should

Dispose waste in landfill or incinerate at any approved facility.

Release the can pressure before disposal of the can.

Section 14 TRANSPORTATION

DOT Labeling:

The combustible liquid n.o.s. label is exempt in containers under 110 gallons. Regulations 49CFR173.118A

Proper Shipping Name:

ORMD. Exempted from compressed gas label. 49CFR 173.306

Identification Number:

UN 1956

Hazard Class:

Non-flammable gas.

Section 15 REGULATORY INFORMATION

OSHA Compliance:

This MSDS prepared in accordance with 29CFR 1910.1200 and ANSI Z400.1 Standard for the preparation of Material Safety Data Sheets.

TSCA:

Although components of this product find listing under the Toxic

SARA Title III Superfund:

CERCLA, State and Local
Planning (R.Q.'s):

State Right-To-Know

Pennsylvania:

Massachusetts:

New Jersey:

California:

Substances Control Act (TSCA) regulations, this blended product requires no import or export regulations.

This product, in its purchased form, is not regulated under the hazard categories of section 311 and 312 of the Superfund Amendment and the Reauthorization Act of 1986 (SARA Title III).
Not required.

Not regulated.

May contain a trace of ethylene oxide, CAS Number 71-21-8.

Not regulated.

In compliance with the Safe Drinking and Toxic Enforcement Act of 1986 (Proposition 65) to provide a clear and reasonable warning, this product may contain a trace of ethylene oxide, CAS Number 71-21-8, which is listed by the Governor of the State of California as required by the Act.

Section 16 OTHER INFORMATION

Hazard Rating:

Health - 2 Flammability - 2 Reactivity - 2.

Based on the NFPA 704 Standard.

None = 0 Slight = 1 Moderate = 2 Severe damage = 3 Extreme = 4

The information expressed herein are those of qualified experts and other reliable sources. We believe that the information contained herein is accurate and current as of the date of this Material Safety Data Sheet. Since the application in use of the information contained herein, and the conditions of use of the product are not under our control; the user must evaluate and determine whether the conditions for use and application of the product, including proper disposal thereof, are appropriate, safe, and legal.